

# MBI Shadow-Coustic® Pad Guide Specification Encapsulated Series 1000P-1515-N

# Part I: General

# 1.1 Work Included:

The work consists of furnishing all labor, materials, accessories and equipment necessary to cover all areas shown on the drawings and specified herein with MBI Panels.

#### 1.2 Delivery and Storage:

Store this product in unopened cartons in a clean, cool, dry interior space. Cartons and product must be protected against marring, water, dirt or damage during delivery and storage.

# Part II: Product

#### 2.1 Product and Manufacturer:

MBI Shadow-Coustic® Acoustical Pads exclusively manufactured by: MBI Products Company, Inc. 801 Bond Street Elyria, OH 44035-3318 Phone: 440.322.6500 Fax: 440.322.1900 Website: www.mbiproducts.com Email: sales@mbiproducts.com

# 2.1.1. Geometric Shape: (Square) (Rectangular)

<u>(Square) (Rectangular)</u>

# 2.1.2 Size & Thickness: <u>1.5" Thick</u>

- 2.1.3 Core: <u>1.5# Fiberglass Core</u>
- 2.1.4 Surface Finish: 1.8 mil PVC
- 2.1.5 Color: 10 Available: See Color Card
- 2.1.6 Edge Shape: Natural

# 2.1.7 Edge Construction: Heat Sealed

#### 2.1.8 Acoustical Performance:

RAL A02-221 E-400 Mtg.					NRC 0.90	
Hz	125	250	500	1000	2000	4000
APU	0.86	0.98	0.81	0.97	0.77	0.52

# 2.1.9 Incombustibility:

<u>Class A per ASTM E84 25/0/50</u>

#### 2.1.10 Suspension Provision:

<u>Placed above metal or planked ceilings by</u> <u>others</u>

# Part III: Execution

# 3.1 Installation

**3.1.1** MBI acoustical panels shall be located and spaced as detailed on reflected ceiling plans and/or detailed on the interior elevation drawings and as indicated on room finish schedule.

#### 3.1.2 Suspend Panels with:

Provided under 2.1.10 per manufacturer's recommendation

#### 3.1.3 Attachment Method:

Provided under 2.1.10 per manufacturer's recommendation

#### 3.1.4 Workmanship

The acoustical system shall be installed only by an approved contractor.

All work shall be completed in a workman like manner. All panels shall be properly installed and left in a clean, sanitary condition. Contractor shall remove and dispose of shipping containers and debris.



MBI Shadow-Coustic® Pad Guide Specification Encapsulated Series 1000P-1515-N