

# MBI Cloud-Lite® Baffle Guide Specification Series 2600P-1030-GGF

Part I: General

#### 1.1 Work Included:

The work consists of furnishing all labor, materials, accessories and equipment necessary to cover all areas shown on the drawings and specified herein with MBI Panels.

## 1.2 Delivery and Storage:

Store this product in unopened cartons in a clean, cool, dry interior space. Cartons and product must be protected against marring, water, dirt or damage during delivery and storage.

## Part II: Product

## 2.1 Product and Manufacturer:

MBI Cloud-Lite® Acoustical Baffles exclusively manufactured by:
MBI Products Company, Inc.
801 Bond Street
Elyria, Ohio 44035-3318

Phone: 440.322.6500 Fax: 440.322.1900

Website: <a href="www.mbiproducts.com">www.mbiproducts.com</a> Email: <a href="mailto:sales@mbiproducts.com">sales@mbiproducts.com</a>

2.1.1 Geometric Shape: Rectangular

**2.1.2 Size & Thickness:** 1" Thick (Maximum size up to 4' x 10')

**2.1.3 Core**: <u>3# Fiberglass</u>

2.1.4 Surface Finish: 2.5 mil PVC

2.1.5 Color: 10 Available: See Color Card

2.1.6 Edge Shape: Natural/Square

2.1.7 Edge Construction: Heat Sealed

## 2.1.8 Acoustical Performance:

RAL A87-122 Type "J" Mtg. 3232 (2'x4') **NRC 1.07**Hz 125 250 500 1000 2000 4000

APU 2.50 3.94 6.72 11.52 12.11 8.69

# 2.1.9 Incombustibility:

Class A per ASTM E84 25/0/50

## 2.1.10 Suspension Provision:

<u>Grommets in Panel / Grommets in Flap</u> (Nickel Plated Brass) (Stainless Steel)

## Part III: Execution

#### 3.1 Installation

**3.1.1** MBI acoustical panels shall be located and spaced as detailed on reflected ceiling plans and/or detailed on the interior elevation drawings and as indicated on room finish schedule.

3.1.2 Suspend Panels From: (horizontal stretched wire or cable) (fasteners [eye screws] [L-Hook]) (existing construction) (see MBI drawings for more information)

## 3.1.3 Attachment Method:

(coated wire tie) (stainless steel tie) (see MBI drawings for more information)

## 3.1.4 Workmanship

The acoustical system shall be installed only by an approved contractor.

All work shall be completed in a workman like manner. All panels shall be properly installed and left in a clean, sanitary condition. Contractor shall remove and dispose of shipping containers and debris.