

# MBI Lapendary® Panel Guide Specification Series 4000S-4075-W, Model #115

### Part I: General

#### 1.1 Work Included:

The work consists of furnishing all labor, materials, accessories and equipment necessary to cover all areas shown on the drawings and specified herein with MBI Panels.

# 1.2 Delivery and Storage:

Store this product in unopened cartons in a clean, cool, dry interior space. Cartons and product must be protected against marring, water, dirt or damage during delivery and storage.

#### Part II: Product

# 2.1 Product and Manufacturer:

MBI Lapendary® Acoustical Panels exclusively manufactured by: MBI Products Company, Inc. 801 Bond Street

Elyria, Ohio 44035-3318 Phone: 440.322.6500 Fax: 440.322.1900

Website: www.mbiproducts.com Email: sales@mbiproducts.com

**2.1.1 Geometric Shape:** Rectangular

2.1.2 Size & Thickness: 4" Thick

(4' x Custom Length)

**2.1.3 Core**: <u>3/4# Fiberglass</u>

2.1.4 Surface Finish:

Nylon Sailcloth, Solid Both Sides

**2.1.5 Color:** 10 Available: See Color Card

2.1.6 Edge Shape: Natural

**2.1.7 Edge Construction** Sewn

2.1.8 Acoustical Performance:

1.00 N.R.C.

**2.1.9 Incombustability:** Class A per ASTM E84 25/0/50

2.1.10 Suspension Provision:

3" Diameter Washer Plates, Painted to Match

#### Part III: Execution

#### 3.1 Installation

**3.1.1** MBI acoustical panels shall be located and spaced as detailed on reflected ceiling plans and/or detailed on the interior elevation drawings and as indicated on room finish schedule.

## 3.1.2 Suspend Panels From:

(existing construction) (cable) (fasteners [type])

#### 3.1.3 Attachment Method:

(heavy duty plastic tie) (coated wire tie) (beam clamps) (washer plates) (cable)

# 3.1.4 Workmanship

The acoustical system shall be installed only by an approved contractor.

All work shall be completed in a workman like manner. All panels shall be properly installed and left in a clean, sanitary condition. Contractor shall remove and dispose of shipping containers and debris.